



# ULTRACRETE MANUFACTURING AND GLOBAL DISTRIBUTION



## ULTRACRETE-REL LIQUID RELEASE AGENT

### PRODUCT SPECIFICATIONS

---

#### COLORLESS BOND BREAKER

**ULTRACRETE-REL** is a colorless bond breaker designed to keep texturing mats from sticking to still-plastic concrete or polymer overlays. **ULTRACRETE-REL** forms a lubricating barrier that prolongs the life of texturing mats by decreasing the friction between the texturing mat and the surface. **ULTRACRETE-REL** requires minimal cleanup and its bubble gum scent makes it easy to use for both indoor and outdoor applications.

#### **BENEFITS**

- Requires very little cleanup.
- Prolongs the life of texturing mats.
- Excellent alternative to powdered release agent.
- Good for use on projects that are to be textured but colored later.
- Typical for both indoor and outdoor applications.
- Pleasant bubble gum scent.

#### **LIMITATIONS**

**ULTRACRETE-REL** is formulated to be used with most texturing mats. However, test a little on texturing mats to insure compatibility before using. To maintain the integrity of the surface, do not trowel or in any way mix the Liquid Release Agent with the surface. To make corrections, use the texturing mat and press out the unwanted impression. No removal of the Liquid Release Agent is necessary.

#### **PACKAGE SIZES/COVERAGE**

Coverage requirements vary depending on timing, method of finishing prior to imprinting, and job or other conditions. For most applications, the coverage rate is approximately 200 square feet per gallon. Available in 1 gallon (**ULTRACRETE-REL1**) and 5 gallon (**ULTRACRETE-REL5**) containers. Also available in 55 gallon drums.

#### **METHOD OF APPLICATION**

Using a pump-up sprayer, liberally apply a mist of **ULTRACRETE-REL** on colored concrete or overlay where you intend to place the next few texturing mats. Do not apply over an area of more than ten to fifteen square feet at a time as the Liquid Release Agent may evaporate before the mats are placed over it.

#### **CLEANING OF TOOLS**

When the texturing application is completed wash off the **ULTRACRETE-REL** from the texturing mats, using plain water and soap.

1-877-485-8721

[WWW.ULTRACRETE.COM](http://WWW.ULTRACRETE.COM)

EMAIL: [WWW.INFO@ULTRACRETE.COM](mailto:WWW.INFO@ULTRACRETE.COM)

*Liquid Release Agent  
Product Specifications  
Page 1 of 2*

**CAUTION! CONTAINS PETROLEUM DISTILLATES**

Combustible liquid. Closed containers may explode when exposed to extreme heat or fire. Keep away from heat, sparks and open flame.

May cause injury to skin following prolonged or repeated contact. Absorption through the skin may be harmful.

- Do not smoke in area where ULTRACRETE-REL is in use.
- Avoid breathing vapors.
- Avoid contact with eyes and skin.
- Flush area with water spray.
- Clean hands thoroughly after use and before smoking or eating.
- Do not take internally.

**AVOID SPILLS**

Keep closure tight and container upright to prevent leakage when not in use. Do not transfer contents to bottles or other unlabeled containers.

In case of spillage, absorb, sweep up, and place in a proper waste disposal container. In case of fire, use foam, dry chemical, or CO2.

**LIMITED WARRANTY**

ULTRACRETE-REL is warranted to be of uniform quality within manufacturing tolerances. Since no control is exercised over their use, no warranty, express or implied, is made as to the effect of such use. Sellers & manufacturer's obligation under this warranty shall be limited to refunding the purchase price of that portion of the material proven to be defective.

21-877-485-8721

[WWW.ULTRACRETE.COM](http://WWW.ULTRACRETE.COM)

EMAIL: [WWW.INFO@ULTRACRETE.COM](mailto:WWW.INFO@ULTRACRETE.COM)

*Liquid Release Agent  
Product Specifications  
Page 2 of 2*